

What is claimed is:

Sub A 6
1. A scroll-type compressor for handling a working fluid, said compressor comprising:

a shell having a suction zone and a discharge zone;

5 a first scroll member disposed in said shell and having a first scroll wrap extending from a first end plate;

a second scroll member disposed in said shell and having a second scroll wrap extending from a second end plate, said second scroll wrap being intermeshed with said first scroll wrap to define a plurality of closed pockets;

10 a drive mechanism for causing said second scroll member to orbit with respect to said first scroll member, said plurality of pockets moving from a radial outer position in said suction zone to a central position in said discharge zone;

a fluid circuit in communication with at least one of said plurality of pockets, said fluid circuit including a fluid passage extending from said one pocket to
15 a position outside said shell, said fluid passage extending through said second scroll member.

2. The scroll-type compressor according to Claim 1, further comprising a housing disposed within said shell, said housing supporting said second scroll member, said fluid passage extending through said housing.

3. The scroll-type compressor according to Claim 2, further comprising a valve disposed within said housing, said valve controlling fluid flow through said fluid passage.

4. The scroll-type compressor according to Claim 3, wherein said valve is controlled by a pressurized fluid from outside said shell.

1

~~2.~~ The scroll-type compressor according to Claim ~~5~~¹, wherein said valve is disposed within said shell.

~~3~~ The scroll-type compressor according to Claim ~~8~~², wherein said valve is controlled by a pressurized fluid from outside said shell.

Sub 18

8. The scroll-type compressor according to Claim 1, further comprising a housing having a plurality of legs disposed within said shell, said housing supporting said first scroll member, said fluid passage extending through one of said legs of said housing.

~~9~~¹². The scroll-type compressor according to Claim ~~8~~¹¹, further comprising a valve disposed within said housing, said valve controlling fluid flow through said fluid passage.

¹³
~~10.~~ The scroll-type compressor according to Claim ¹²~~9~~, wherein said valve is controlled by a pressurized fluid from outside said shell.

Sub A9

11. A scroll-type compressor for handling a working fluid; said compressor comprising:
- 5 a shell;
- a non-orbiting scroll member disposed within said shell and having a non-orbiting scroll wrap extending from a non-orbiting end plate;
- an orbiting scroll member disposed within said shell and having an orbiting scroll wrap extending from an orbiting end plate, said orbiting scroll wrap being intermeshed with said non-orbiting scroll member to define a plurality of closed pockets;
- 10 a drive mechanism for causing said orbiting scroll member to orbit with respect to said non-orbiting scroll member, said plurality of closed pockets moving from a radial outer position where said working fluid is at a suction pressure to a radially inner central position where said working fluid is at a higher discharge pressure during said orbital movement;
- 15 a fluid circuit in communication with at least one of said plurality of moving pockets, said fluid circuit including a fluid passage extending from said one pocket to a position outside of said shell, said fluid pocket extending through said orbiting scroll member.

12. The scroll-type compressor according to Claim 11, further comprising a housing disposed within said shell, said housing supporting said orbiting scroll member, said fluid passage extending through said housing.

13. The scroll-type compressor according to Claim 12, further comprising a valve disposed within said housing, said valve controlling fluid flow through said fluid passage.

Sub A10

14. The scroll-type compressor according to Claim 13, wherein said valve is controlled by a pressurized fluid from outside said shell.

15. The scroll-type compressor according to Claim 11 further comprising a valve for controlling fluid flow through said fluid passage.

⁵
~~16.~~ The scroll-type compressor according to Claim ⁴~~15~~, wherein said valve is disposed within said shell.

⁶
~~17.~~ The scroll-type compressor according to Claim ⁵~~16~~, wherein said valve is controlled by a pressurized fluid from outside said shell.

09:33:33 11:04:51

Sub A11

18. The scroll-type compressor according to Claim 1, further comprising a housing having a plurality of legs disposed within said shell, said housing supporting said orbiting scroll member, said fluid passage extending through one of said legs of said housing.

¹⁵
~~19.~~ The scroll-type compressor according to Claim ¹⁴~~18~~, further comprising a valve disposed within said one leg of said housing, said valve controlling fluid flow through said fluid passage.

¹⁴
~~20.~~ The scroll-type compressor according to Claim ¹⁵~~19~~, wherein said valve is controlled by a pressurized fluid from outside said shell.

21. A scroll-type compressor for handling a working fluid, said compressor comprising:

a shell having a suction zone and a discharge zone;

5 a first scroll member disposed in said shell and having a first scroll wrap extending from a first end plate;

a second scroll member disposed in said shell and having a second scroll wrap extending from a second end plate, said second scroll wrap being intermeshed with said first scroll wrap to define a plurality of closed pockets;

10 a drive mechanism for causing said second scroll member to orbit with respect to said first scroll member, said plurality of pockets moving from a radial outer position in said suction zone to a central position in said discharge zone;

15 a fluid circuit in communication with at least one of said plurality of pockets, said fluid circuit including a fluid passage extending from said one pocket to said suction zone of said compressor, said fluid passage extending through said second scroll member.

22. The scroll-type compressor according to Claim 21, wherein said first scroll member is a non-orbiting scroll and said second scroll member is an orbiting scroll.

Sub A12
23. The scroll-type compressor according to Claim 21, further comprising a housing disposed within said shell, said housing supporting said second scroll member, said fluid passage extending through said housing.

18
24. *17*
The scroll-type compressor according to Claim 23, further comprising a valve disposed within said housing, said valve controlling fluid flow through said fluid passage.

19
25.

18

The scroll-type compressor according to Claim 24, wherein said valve is controlled by a pressurized fluid from outside said shell.

Sub Q⁽¹³⁾

26. The scroll-type compressor according to Claim 24, wherein said valve is movable between a first position where said fluid passage communicates with said suction zone of said compressor and a second position where said fluid passage communicates with a position outside said shell.

27. The scroll-type compressor according to Claim 21, further comprising a valve for controlling fluid flow through said fluid passage.

28. The scroll-type compressor according to Claim 27, wherein said valve is disposed within said shell.

29. The scroll-type compressor according to Claim 28, wherein said valve is controlled by a pressurized fluid from outside said shell.

Sub Q⁽¹⁴⁾

30. The scroll-type compressor according to Claim 27, wherein said valve is movable between a first position where said fluid passage communicates with said suction zone of said compressor and a second position where said fluid passage communicates with a position outside said shell.

31. The scroll-type compressor according to Claim 21, further comprising a housing having a plurality of legs disposed within said shell, said housing supporting said first scroll member, said fluid passage extending through one of said legs of said housing.

~~24~~
~~32.~~

The scroll-type compressor according to Claim ~~31~~²³, further comprising a valve disposed within said housing, said valve controlling fluid flow through said fluid passage.

~~25~~
~~33.~~

The scroll-type compressor according to Claim ~~32~~²⁴, wherein said valve is controlled by a pressurized fluid from outside said shell.

09030004 004500